



# Installation Notes for Garmin Zumo 550 with Kennedy Technology Group CellSet MC/GPS ICS/MIC on a GL1800 Gold Wing

Document Part Number: 65433R0

The diagram at the left is designed as an aid to the installer in connecting a Garmin Zumo 550 to a Gold Wing GL1800. This diagram assumes that the Zumo is being installed with CellSet MC/GPS. ICS/MIC (part number 95413), and that no other audio devices (e.g. iPod, Sirius, etc.) are being connected. If you have additional parts other than those shown this diagram will not suffice. Consult the directions for the components you have, and contact Kennedy Technology Group, 316-776-1111, or [kennedy@cellset.com](mailto:kennedy@cellset.com) if you need further specific assistance.

## Notes on Locating Connectors on the GL1800

The three connections to the bike (Intercom, Aux, and Power) are accessed by removing the left fairing pocket of the motorcycle. This pocket is held in by four nylon fasteners. For 2006+ bikes, you must remove the trim strip that runs along the left side of the pocket to expose two of the fasteners. This isn't necessary on 2001-2005 bikes.

To remove the fasteners, poke the center portion in with a pair of needle nose pliers, then grasp the outer ring with the pliers and lift the fastener out. When all four fasteners are out, lift the pocket out of the opening.

If the pocket has a cigarette socket or Aux Audio pigtail installed, follow those leads to their respective sockets and disconnect them. Make note of the locations of those plugs on the bike, because those are two of the connections you'll use to install this interface.

If you don't have the cigarette socket or aux pigtail installed, then you'll need to locate the aux audio and power socket in the area under the pocket. The two connections will be found together, generally with a black vinyl sleeve surrounding both of them. The aux audio is a 3-pin white flat connector, and the power is a dark red connector with 2 wires leading to it.

The intercom connection location varies depending on the model year of the motorcycle. On all years, however, you can follow the cable from the rider's 5-pin headset lead to locate the red plug at the end of that lead. On 2001-2002 bikes the connection will be near the power & aux audio and easy to reach. 2003-2005 models usually have the connection down below and to the right within the pocket opening, and it may be necessary to remove the Headlight Adjust panel (the panel directly below the fairing pocket) to find the intercom plug. On 2006 and later bikes, the connection is usually found beneath the air intake on the right hand side of the area beneath the pocket. In any event, you should not have to remove anything other than the pocket itself and perhaps the headlight adjustment panel to locate the dark red intercom connector.

