


A B C D E F G H J K L M N P

Rev	Description	By	Date
0	Release	--	06/28/05



Note: Do not crimp tinned wires.
Crimp to include part of braid's heatshrink

Item	Part #	Rev	Qty	Unit	Description
10	70019	0	1	ea	Bag, Zipper, 2 mil, 5 x 5
9	65200	1	1	ea	user/Install sheet, cell phone cable
8	60131	0	1	ea	Label, Cell phone cable, IPAQ, long
7	60049	0	1	ea	label, overlaminating, 1.25 x 3
6	40189	0	1	ea	Cordset, plug, 3.5 mm, 4 cond., 6 ft, right angle
5	40153	0	2	ea	Terminal, Female, Micro-fit, gold, 26-30 AWG
4	40133	0	1	ea	Receptacle, Micro-fit, 4 circuit
3	40118	0	1	ea	Terminal, Female, Micro-fit, gold, 20-24 AWG
2	30049	0	1	in	Tubing, heat shrink, 1/16
1	30034	0	1	in	Tubing, heat shrink, 1/8"

THIS DRAWING IS THE PROPERTY OF THE KENNEDY TECHNOLOGY GROUP, ROSE HILL, KANSAS

Kennedy Technology

REFERENCE: 95300R1 Cordset, cell phone, IPAQ

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES
LINEAR
Fractional - 1/32"
0.0 ± 0.15
0.01 ± 0.015
0.000 ± 0.0015
ANGULAR
±0.5 DEG.

SIZE: B CADFILE: DWG NO. 95365 REV NO. 0 EFFECTIVE sn:

SCALE: NONE FOR ASSISTANCE CONTACT: DRAWN DATE
SHEET 1 OF 1 vox 316-776-1111 CHECKED DATE
fax 316-776-9035

A B C D E F G H J K L M N P